



BOMBILLAS DE BAJO CONSUMO

"LED"



Modelo	LED SPOT	LED SPOT	LED SPOT		LED Minispot	LED Minispot	LED Minispot	LED Minispot	LED Minispot	LED Minispot
Unidades LED	3	3	3		48	48	48	48	48	48
Potencia	3W ≅ 25W	3W ≅ 25W	3W ≅ 25W		2W ≅ 20W	2W ≅ 20W	2W ≅ 20W	2W ≅ 20W	2W ≅ 20W	2W ≅ 20W
Rosca	GU10	E14	E27		GU10	GU10	E14	E14	E27	E27
Kelvin	2800 K	2800 K	2800 K		6500 K	2800 K	6500 K	2800 K	2800 K	2800 K
Ángulo de acción	30°	30°	30°		30°	30°	30°	30°	30°	30°
Luz	cálida / blanca	cálida / blanca	cálida / blanca		Daylight / DIA	cálida / blanca	Daylight / DIA	cálida / blanca	Daylight / DIA	cálida / blanca
Tº ambiente de utilización	-35°C --> 50°	-35°C --> 50°	-35°C --> 50°		-35°C --> 50°	-35°C --> 50°	-35°C --> 50°	-35°C --> 50°	-35°C --> 50°	-35°C --> 50°
Certificados	CE / RoHS	CE / RoHS	CE / RoHS		CE / RoHS	CE / RoHS	CE / RoHS	CE / RoHS	CE / RoHS	CE / RoHS
Tamaño	48 x 58 mm	48 x 74 mm	48 x 58 mm		48 x 64 mm	48 x 64 mm	48 x 76 mm	48 x 76 mm	48 x 74 mm	48 x 76 mm
lumen (lm)	260 lm	260 lm	260 lm		170 lm	160 lm	170 lm	160 lm	170 lm	160 lm
Vida	35.000 horas	35.000 horas	35.000 horas		35.000 horas	35.000 horas	35.000 horas	35.000 horas	35.000 horas	35.000 horas
Referencia	399 20001	399 20002	399 20003		399 20005	399 20006	399 20007	399 20008	399 20009	399 10010
Línea	CPH019	CPH019	CPH019		CLT019	CLT019	CLT019	CLT019	CLT019	CLT019





BOMBILLAS DE BAJO CONSUMO

"LED"



Modelo	LED LIGHT	LED LIGHT	LED GLOBE	LED CANDLE	LED CANDLE	LED CANDLE	LED CANDLE	LED CANDLE	LED CANDLE
Unidades LED	5	10	168	86	90	90	90	90	90
Potencia	6W ≅ 40W	5W ≅ 40W	6,5W ≅ 45W	4W ≅ 30W	5W ≅ 40W	5W ≅ 40W	5W ≅ 40W	5W ≅ 40W	5W ≅ 40W
Rosca	E27	E27	E27	E14	E14	E14	E14	E27	E27
Kelvin	3000 K	2800 K	3000 K	3000 K	2800 K	6500 K	2800 K	2800 K	6500 K
Ángulo de acción	120 °	120 °	180°	180°	120 °	120 °	120 °	120 °	120 °
Luz	cálida / blanca	cálida / blanca	cálida / blanca	cálida / blanca	cálida / blanca	Daylight / DIA	cálida / blanca	Daylight / DIA	Daylight / DIA
Tº ambiente de utilización	-35°C --> 50°	-35°C --> 50°	-35°C --> 50°	-35°C --> 50°	-35°C --> 50°	-35°C --> 50°	-35°C --> 50°	-35°C --> 50°	-35°C --> 50°
Certificados	CE / RoHS	CE / RoHS	CE / RoHS	CE / RoHS	CE / RoHS	CE / RoHS	CE / RoHS	CE / RoHS	CE / RoHS
Tamaño	60 x 117 mm	60 x 118 mm	65 x 125 mm	42 x 133 mm	42 x 126 mm	42 x 126 mm	42 x 126 mm	42 x 126 mm	42 x 126 mm
lumen (lm)	480 LM	380 LM	600 LM	300 LM	370 LM	380 LM	370 LM	370 LM	380 LM
Vida	35.000 horas	35.000 horas	35.000 horas	35.000 horas	35.000 horas	35.000 horas	35.000 horas	35.000 horas	35.000 horas
Referencia	399 20004	399 20019	399 20012	399 20014	399 20015	399 20016	399 20017	399 20018	
Línea	CHP040	BLH60	CLF020	CLQ015	BLG42	BLG42	BLG42	BLG42	BLG42

